

EXCEL EMULSION

PRODUCT DESCRIPTION

Emirates Excel Emulsion is a vinyl-acrylic copolymer based paint, engineered to provide a matt decorative finish.

PRODUCT FEATURES

- Water based
- General purpose
- Excellent recoat ability and strong hiding power
- Extreme surface coverage with fewer coats
- Leveling property
- Weather resistant
- Anti-bacterial, anti-fungal and anti-algae

RECOMMENDED USE

This product is recommended for application on concrete, plaster, brickwork, asbestos and wooden surfaces.

*Used for interior applications.

TECHNICAL SPECIFICATIONS

Color	Refer to Emirates Paints shade card
Finish	Matt
Spreading Rate	10 - 11 m ² / litre
Volume Solids (ASTM d2697)	45 ± 2%
Specific Gravity	1.50 ± 0.05
Dry Film Thickness	50 Microns/ Coat
Wet Film Thickness	100 Microns/ Coat
Packaging Size	3.6L + 18L
Flash Point	Water Based



EXCEL EMULSION

APPLICATION DATA

Application Method	Brush, Roller, Spray
Thinner	10% water maximum depending on the method of application
Airless Spray Requirements	Nozzle Size: 0.018" – 0.021" Pressure: 2000 – 2500 psi

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

Touch Dry	55 - 60 minutes
Dry to Recoat	2 - 3 hours
Full Dry	8 - 12 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Emirates PVA Primer Sealer for Masonry (W.B) or PVA Primer for Masonry or Acrylic Primer WB	1 Coat
Emirates Stucco Filler	2 Coats
Emirates Excel Emulsion	2 Coats



EXCEL EMULSION

HEALTH & SAFETY

Water based paints are generally quite safe when handled with precaution, we highly recommend you follow your local safety regulations. Avoid inhalation of vapors and paint mist by painting in a well-ventilated area with a suitable mask. As a general rule, please avoid skin and eye contact by wearing the appropriate protective gear. However, if spillage occurs please wash with water. In the case of eye contact and/or ingestion seek medical attention immediately.

STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

