

EMASHIELD EXTERIOR PUTTY

PRODUCT DESCRIPTION

Emirates Emashield Exterior Putty is a 100% pure acrylic-based homogenous putty with specially graded fillers, engineered to provide a uniform surface offering maximum performance to topcoat.

PRODUCT FEATURES

- Easy to apply
- Enhanced with advanced adhesion
- Excellent body filling
- Hides surface imperfections
- Maximum performance to topcoats
- Less volume shrinkage after dry
- Excellent filler for porosity of concrete
- Exceptional durability

RECOMMENDED USE

This product is recommended for application on concrete surfaces, hollow concrete blocks and plaster surfaces. Ideal for leveling and filling of surface imperfections.

*Used for exterior applications.

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|----------------------------------|
| Color | White |
| Finish | Matt |
| Spreading Rate | 3.0 - 6.5 m ² / litre |
| Volume Solids (ASTM d2697) | 64 ± 2% |
| Specific Gravity | 1.72 ± 0.05 |
| Dry Film Thickness | 100 - 200 microns / coat |
| Wet Film Thickness | 155 - 310 microns / coat |
| Flash Point | Water Based |



EMASHIELD EXTERIOR PUTTY

APPLICATION DATA

| | |
|--------------------|-------------------------------|
| Application Method | Scrapper, Putty Knife, Trowel |
| Thinner | Ready to Use, Water |

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

| | |
|---------------|-------------|
| Touch Dry | 1 - 2 hours |
| Dry to Recoat | 4 - 6 hours |
| Full Dry | 24 hours |

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.



EMASHIELD EXTERIOR PUTTY

HEALTH & SAFETY

Water based paints are generally quite safe when handled with precaution, we highly recommend you follow your local safety regulations. Avoid inhalation of vapors and paint mist by painting in a well-ventilated area with a suitable mask. As a general rule, please avoid skin and eye contact by wearing the appropriate protective gear. However, if spillage occurs please wash with water. In the case of eye contact and/or ingestion seek medical attention immediately.

STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

