

STUCCO FILLER

PRODUCT DESCRIPTION

Emirates Stucco Filler is a PVA copolymer-based high solid putty with graded fillers, engineered to conceal surface flaws or dents while providing a matt finish.

PRODUCT FEATURES

- Water based
- General purpose
- Enhanced with advanced adhesion
- Excellent recoatability and strong hiding powder
- Extreme surface coverage with fewer coats
- Excellent and fast sandability
- Anti-bacterial, anti-fungal and anti-algae

RECOMMENDED USE

This product is recommended for application on masonry, concrete, plaster, gypsum and wooden surfaces.

*Best used for interior applications only.

TECHNICAL SPECIFICATIONS

Color	White
Finish	Matt
Spreading Rate	6 m ² / litre
Volume Solids (ASTM d2697)	60 ± 2%
Specific Gravity	1.70 ± 0.05
Dry Film Thickness	80 Microns / Coat
Wet Film Thickness	160 Microns / Coat
Packaging Size	3.6L + 18L
Flash Point	Water Based



STUCCO FILLER

APPLICATION DATA

Application Method Putty Knife, Glazing Knife, Scraper

Thinner Ready for use

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

Touch Dry 40 - 55 minutes

Dry to Recoat 2 - 3 hours

Full Dry 7 - 8 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Emirates PVA Primer for Masonry or
Emirates Acrylic Primer White WB 1 Coat

Emirates Stucco Filler 2 Coats



STUCCO FILLER

HEALTH & SAFETY

Water based paints are generally quite safe when handled with precaution, we highly recommend you follow your local safety regulations. Avoid inhalation of vapors and paint mist by painting in a well-ventilated area with a suitable mask. As a general rule, please avoid skin and eye contact by wearing the appropriate protective gear. However, if spillage occurs please wash with water. In the case of eye contact and/or ingestion seek medical attention immediately.

STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

