

EMASHIELD LONG LIFE ANTIQUE TEX

PRODUCT DESCRIPTION

Emirates Emashield Long Life Antique Tex is a pure acrylic emulsion-based paint, designed to provide a matt attractive antique finish.

PRODUCT FEATURES

- Water based
- Enhanced with advanced adhesion and durability
- Premium quality aggregates
- Excellent crack-bridging ability
- Low dirt pick up
- UV resistance
- Weather and water resistant
- Anti-carbonation coating
- Alkali resistant
- Anti-bacterial, anti-fungal and anti-algae

RECOMMENDED USE

This product is recommended for application on concrete, gypsum, plaster, brickwork, asbestos and masonry surfaces.

*Used for exterior applications.

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|-------------------------------------|
| Color | Refer to Emirates Paints shade card |
| Finish | Matt, Antique Texture |
| Spreading Rate | 0.6 - 1.20 m ² / litre |
| Volume Solids (ASTM d2697) | 62 ± 2% |
| Specific Gravity | 1.55 ± 0.05 |
| Dry Film Thickness | 500 - 1000 Microns / Coat |
| Wet Film Thickness | 800 - 1600 Microns / Coat |
| Packaging Size | 3.6L + 18L |
| Flash Point | Water Based |



EMASHIELD LONG LIFE ANTIQUE TEX

APPLICATION DATA

| | |
|--------------------|---|
| Application Method | Spray, Roller, Brush |
| Thinner | 10% Water maximum by volume depending on the application method |

SURFACE PREPARATION

The Surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

| | |
|---------------|---------------|
| Touch Dry | 2 - 3 hours |
| Dry to Recoat | 6 - 8 hours |
| Full Dry | 24 - 48 hours |

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

| | |
|--|---------|
| Emirates Acrylic Primer WB | 1 Coat |
| Emirates Emashield Long Life Antique Tex | 2 Coats |



EMASHIELD LONG LIFE ANTIQUE TEX

HEALTH & SAFETY

Water based paints are generally quite safe when handled with precaution, we highly recommend you follow your local safety regulations. Avoid inhalation of vapors and paint mist by painting in a well-ventilated area with a suitable mask. As a general rule, please avoid skin and eye contact by wearing the appropriate protective gear. However, if spillage occurs please wash with water. In the case of eye contact and/or ingestion seek medical attention immediately.

STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

