

SPRAY PLASTER COARSE

PRODUCT DESCRIPTION

Emirates Spray Plaster Coarse is an acrylic copolymer-based spray binder with special fillers, engineered to provide a rough, hard finish.

PRODUCT FEATURES

- Internal ready mixed plaster
- Easy application
- Excellent adhesion
- Ready-to-use and pre-blended
- Weather resistance
- Absence of chloride additives
- Economical
- Minimal shrinkage after dry
- Anti-bacterial, anti-fungal and anti-algae

RECOMMENDED USE

This product is recommended for application on concrete, masonry surfaces, brickworks and as a base coat on ground floors. Don't use it on surfaces subjected to continuous leakage.

*Used for interior applications only.

TECHNICAL SPECIFICATIONS

Color	Off White
Finish	Rough, Hard
Spreading Rate	3.0 kg / m ² / mm (depending on the surface)
Volume Solids (ASTM d2697)	61 ± 2%
Specific Gravity	1.83 ± 0.05
Dry Film Thickness	5000 Microns / Coat
Wet Film Thickness	8000 Microns / Coat
Packaging Size	25kg Plastic Bag
Flash Point	Water Based



SPRAY PLASTER COARSE

APPLICATION DATA

Application Method	Putty knife, Scraper, Spray
Thinner	Ready to use, 5% Water maximum by volume, if required

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

Touch Dry	3 - 4 hours
Dry to Recoat	24 hours
Full Dry	48 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Emirates Spray Plaster Coarse	1 Coat
Emirates Spray Plaster Medium	1 Coat
Emirates Spray Plaster Fine (Smooth or Textured)	1 - 2 Coats



SPRAY PLASTER COARSE

HEALTH & SAFETY

Water based paints are generally quite safe when handled with precaution, we highly recommend you follow your local safety regulations. Avoid inhalation of vapors and paint mist by painting in a well-ventilated area with a suitable mask. As a general rule, please avoid skin and eye contact by wearing the appropriate protective gear. However, if spillage occurs please wash with water. In the case of eye contact and/or ingestion seek medical attention immediately.

STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

