

# MAJESTIC SILK

## PRODUCT DESCRIPTION

Emirates Majestic Silk is an acrylic polymer-based emulsion paint, engineered to provide a long lasting silk finish.

## PRODUCT FEATURES

- Water based
- Enhanced with advanced adhesion
- Enhanced washability
- Extreme surface coverage with fewer coats
- Easy application
- Low odor
- Alkali resistant
- Anti-bacterial, anti-fungal and anti-algae

## RECOMMENDED USE

This product is recommended for application on masonry, concrete, cement and plaster surfaces.

\*Best used for interior applications only.

## TECHNICAL SPECIFICATIONS

|                            |   |
|----------------------------|---|
| Color                      | Refer to Emirates Paints shade card       |
| Finish                     | Silk                                      |
| Spreading Rate             | 10 - 12 m <sup>2</sup> / litre            |
| Volume Solids (ASTM d2697) | 35 ± 2%                                   |
| Specific Gravity           | 1.30 ± 0.05 (For white and pastel colors) |
| Dry Film Thickness         | 30 - 40 Microns / Coat                    |
| Wet Film Thickness         | 80 - 100 Microns / Coat                   |
| Packaging Size             | 3.6L + 18L                                |
| Flash Point                | Water Based                               |



## MAJESTIC SILK

### APPLICATION DATA

|                            |   |
|----------------------------|---|
| Application Method         | Brush, Roller, Spray  |
| Thinner                    | 10% Water maximum by volume depending on the application method                     |
| Airless Spray Requirements | Nozzle Size: 0.021 – 0.027"<br>Pressure: 2100 psi<br>Spray Angle: 650 - 800 degrees |

### SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

### DRY TIME

|               |              |
|---------------|--------------|
| Touch Dry     | 1 - 3 hours  |
| Dry to Recoat | 4 - 6 hours  |
| Full Dry      | 8 - 12 hours |

\*Based on temperatures at 30 degrees Celsius.

\*Humidity, air movement, film thickness and number of coats may impact dry time.

### RECOMMENDED SYSTEM

|                            |         |
|----------------------------|---------|
| Emirates Acrylic Primer WB | 1 Coat  |
| Emirates Stucco Filler     | 2 Coats |
| Emirates Majestic Silk     | 2 Coats |



## MAJESTIC SILK

---

### HEALTH & SAFETY

Water based paints are generally quite safe when handled with precaution, we highly recommend you follow your local safety regulations. Avoid inhalation of vapors and paint mist by painting in a well-ventilated area with a suitable mask. As a general rule, please avoid skin and eye contact by wearing the appropriate protective gear. However, if spillage occurs please wash with water. In the case of eye contact and/or ingestion seek medical attention immediately.

---

### STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

---

### SHELF LIFE

\*For best results, please use within 18 months of the production date.

\*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

---

### DISCLAIMER

*The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.*

---

