

# EMAPOXY SB FLOORING TOPCOAT

## PRODUCT DESCRIPTION

Emirates Emapoxy SB Flooring Topcoat is a two-pack polyamide-cured epoxy resin-based topcoat, engineered with excellent flow properties and a glossy finish.

## PRODUCT FEATURES

- Washable
- Fully cured film
- Enhanced with advanced adhesion
- Good flow abrasion
- Impact resistant
- Water resistant
- Chemicals resistant

## RECOMMENDED USE

This product is recommended for application on cementitious surfaces, concrete and light-duty floors.

## TECHNICAL SPECIFICATIONS

Color	Limited Pastel Colors
Finish	Gloss
Spreading Rate	5.5 - 11 m <sup>2</sup> / litre
Volume Solids (ASTM D2697)	55 ± 2%
Specific Gravity	1.40 ± 0.05
Dry Film Thickness	50 - 100 Microns / Coat
Wet Film Thickness	90 - 180 Microns / Coat
Packaging Size	3.6L + 18L
Flash Point	25° C



# EMAPOXY SB FLOORING TOPCOAT

## APPLICATION DATA

Application Method	Brush, Roller, Spray
Thinner	5 - 10% Emirates Epoxy Thinner depending on the application method
Airless Spray Requirements	Nozzle Size: 0.018" – 0.020" Pressure: 2000 - 2200 psi
Mixing Ratio by Volume	4 :1 (Base:Hardener) Mix properly, keep for 15 - 20 minutes before use
Pot Life @30° C	6 - 8 hours

## SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

## DRY TIME

Touch Dry	3 - 6 hours
Dry to Recoat	12 - 72 hours
Full Dry	7 days

\*Based on temperatures at 30 degrees Celsius.

\*Humidity, air movement, film thickness and number of coats may impact dry time.

## RECOMMENDED SYSTEM

Emirates Emapoxy Primer for Cement Clear	1 Coat
Emirates Emapoxy SB Flooring Topcoat	2 Coats

Note:

\*Spread recommended size aggregates when the first coat is wet.

\*Apply the second coat as a topcoat after 24 hours.



## EMAPOXY SB FLOORING TOPCOAT

### HEALTH & SAFETY

*Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.*

### STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use

### SHELF LIFE

\*For best results, please use within 18 months of the production date.

\*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

### DISCLAIMER

*The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.*

