

ALUMINIUM PAINT

PRODUCT DESCRIPTION

Emirates Aluminium Paint is formulated with pure metallic aluminum flakes dispersed in a special synthetic binder, which provides maximum brightness and reflectance, with heat resistance up to 250°C.

PRODUCT FEATURES

- Excellent heat and light reflection
- Outstanding water resistance
- Excellent heat stability
- Bright, shiny decorative Finish
- Heat resistance up to 250°C

RECOMMENDED USE

This product is recommended for heat-resistant coating for electric poles, exhaust pipes, radiators, iron towers, pipes, etc. It can also be used as a protective and decorative coating, over primed metals and wooden surfaces.

*Used for Industrial applications.

TECHNICAL SPECIFICATIONS

Color	Aluminium
Finish	Metallic / Lustrous
Spreading Rate	13.2 m ² / litre
Volume Solids	33 ± 2%
Specific Gravity	0.95 ± 0.05
Dry Film Thickness	25 Microns/Coat
Wet Film Thickness	75 Microns/Coat
Packaging Size	0.9L + 3.6L + 18L
Flash Point	25° C



ALUMINIUM PAINT

APPLICATION DATA

Application Method	Brush, Roller, Spray
Thinner	Emirates GP Thinner
Conventional Spray Requirements	Ready to use
Airless Spray Requirements	Nozzle Size: 2200 psi Pressure: 40 psi
Mixing Ratio (By Volume)	0.016" – 0.018"
Pot life @30°C	NA

SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

DRY TIME

Touch Dry	20 – 45 minutes
Dry to Recoat	6 – 8 hours
Full Dry	48 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Emirates Aluminium Paint	2 Coats
Emirates Red Oxide Primer	1 Coat



ALUMINIUM PAINT

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

SHELF LIFE

**For best results, please use within 18 months of the production date.*

**Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.*

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

