

EMA PU WOOD CLEAR SEMI-GLOSS (2:1)

PRODUCT DESCRIPTION

Emirates Ema PU Wood Clear Semi-Gloss (2:1) is a fast-drying, two-component Polyurethane based wood clear, designed to provide excellent resistance to water and abrasion for wooden surfaces.

PRODUCT FEATURES

- Two-pack system with long pot life
 - Easy to apply
 - Good coverage
 - Excellent adhesion to wooden surfaces
- Excellent UV resistance properties.

RECOMMENDED USE

This product is recommended for Wooden surfaces for all architectural purposes, carpentry work, furniture, etc.

*Used for interior and exterior applications.

TECHNICAL SPECIFICATIONS

Color	Clear
Finish	Semi-Gloss
Spreading Rate	10 M ² / Litre
Volume Solids	30 ± 2%
Specific Gravity	1.00 ± 0.05 (Mixed)
Dry Film Thickness	30 Microns/Coat (Minimum) depends on nature of wood
Wet Film Thickness	100 Microns/Coat (Minimum) depends on nature of wood
Packaging Size	1.5L + 5.4L + 27L
Flash Point	25°C



EMA PU WOOD CLEAR SEMI-GLOSS (2:1)

APPLICATION DATA

Application Method	Conventional Spray or Auto spray
Thinner	Emirates Polyurethane Thinner (15 - 20% depends on method of application)
Conventional Spray Requirements	Possible
Mixing Ratio by Weight	2:1 (Base : Hardener), (Mix properly keep for 10-15 minutes before use)
Pot life @30°C (100 ml)	8 hours

SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

DRY TIME

Touch Dry	5 - 10 minutes
Dry to Recoat	30 minutes
Full Dry	24 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Emirates Ema PU Wood Sanding Sealer (2:1)	2 - 3 Coats
Emirates Ema PU Wood Clear Semi-Gloss (2:1)	1 - 2 Coats



EMA PU WOOD CLEAR SEMI-GLOSS (2:1)

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

