

# EMA PU WOOD TOPCOAT MATT (2:1)

## PRODUCT DESCRIPTION

Emirates Ema PU Wood Topcoat Matt (2:1) is a two-pack polyurethane-based topcoat, engineered to provide excellent water resistance and adhesion to wooden surfaces.

## PRODUCT FEATURES

- Two-pack system for better durability
- Excellent U.V. resistance
- Easy application
- Excellent adhesion
- Water resistance
- High Coverage

## RECOMMENDED USE

This product is recommended for wooden surfaces for all architectural purposes.

\*Used for interior and exterior applications.

## TECHNICAL SPECIFICATIONS

Color	As per Emirates Paints shade card
Finish	Matt
Spreading Rate	8.5 m <sup>2</sup> / litre
Volume Solids (ASTM d2697)	35 ± 2%
Specific Gravity	1.15 ± 0.05 (Mixed)
Dry Film Thickness	40 Microns / Coat
Wet Film Thickness	115 Microns / Coat
Packaging Size	1.5L + 5.4L + 27L
Flash Point	25° C



## EMA PU WOOD TOPCOAT MATT (2:1)

### APPLICATION DATA

Application Method	Conventional Spray or Auto spray
Thinner	Emirates PU Thinner (15 – 20% depending on the application method)
Conventional Spray Requirements	Possible
Mixing Ratio by Weight	2 : 1 (Base: Hardener), (Mix properly, keep 10 – 15 minutes before use)
Pot life @30°C (100 ml)	8 hours

### SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles prior to application.

### DRY TIME

Touch Dry	2 - 3 hours
Dry to Recoat	8 hours
Full Dry	24 hours

\*Based on temperatures at 30 degrees Celsius.

\*Humidity, air movement, film thickness and number of coats may impact dry time.

### RECOMMENDED SYSTEM

Emirates PU Wood Primer White (2:1)	2 Coats
Emirates Ema PU Wood Topcoat Matt (2:1)	1 - 2 Coats



## EMA PU WOOD TOPCOAT MATT (2:1)

### HEALTH & SAFETY

*Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.*

### STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

### SHELF LIFE

\*For best results, please use within 18 months of the production date.

\*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

### DISCLAIMER

*The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.*

