

EMACRYLIC TOPCOAT MATT

PRODUCT DESCRIPTION

Emirates Emacrylic Topcoat Matt is a special polymer solution and an acrylic-based topcoat, engineered to be long-lasting and solvent-based, providing a matt finish.

PRODUCT FEATURES

- Solvent based
- Easy application
- Excellent water resistance
- UV resistant

RECOMMENDED USE

This product is recommended for application on cement, steel and wooden surfaces.

*Used for interior and exterior applications.

TECHNICAL SPECIFICATIONS

Color	Refer to Emirates Paints shade card
Finish	Matt
Spreading Rate	11.5 - 15 m ² / litre
Volume Solids (ASTM D2697)	46 ± 2%
Specific Gravity	1.32 ± 0.05
Dry Film Thickness	30 - 40 Microns / Coat
Wet Film Thickness	65 - 90 Microns / Coat
Packaging Size	3.6L + 18L
Flash Point	32° C



EMACRYLIC TOPCOAT MATT

APPLICATION DATA

Application Method	Brush, Roller, Spray
Thinner	5 - 15% Emirates Acrylic Thinner
Airless Spray Requirements	Nozzle Size: 0.018" – 0.020" Pressure: 2100 psi

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

Touch Dry	30 minutes
Dry to Recoat	3 - 4 hours
Full Dry	24 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

For Cementitious Surfaces:

Emirates Acrylic Primer WB	30 Microns
Emirates Nutex (Spray Texture)	500 Microns
Emirates Emacrylic Topcoat	80 Microns

For Steel and Metal Surfaces:

Emirates Emapoxy Zinc Phosphate Primer	50 Microns
Emirates Emacrylic Topcoat	80 Microns



EMACRYLIC TOPCOAT MATT

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

