

# EMAPOXY SF TOPCOAT PIGMENTED

## PRODUCT DESCRIPTION

Emirates Emapoxy SF Topcoat Pigmented is a two-component heavy-duty coating that provides a high gloss, seamless, hygienic surface that is tough wearing, durable, Antimicrobial Finish.

## PRODUCT FEATURES

- Excellent gloss
- Antimicrobial
- Impact and Abrasion Resistance
- Tough wearing
- Smooth and Durable Finish

## RECOMMENDED USE

This product is recommended for heavy-duty applications for the protection of cementitious surfaces and flooring applications of workshops, kitchens, breweries, beverage plants and stores, cold storage, garages, malls, etc.

\*Used for Industrial applications.

## TECHNICAL SPECIFICATIONS

Color	As per Emirates Paints' Shade Card
Finish	Gloss
Spreading Rate	4.95 M <sup>2</sup> / Litre
Volume Solids (% by volume)	99 ± 1%
Specific Gravity	1.10- 1.2 (mixed)
Dry Film Thickness	200 Microns / Coat
Packaging Size	25KG + 5KG + 1.25KG
Flash Point	68°C



## EMAPOXY SF TOPCOAT PIGMENTED

### APPLICATION DATA

Application Method	Trowel, Mohair roller followed by spike roller
Thinner	Emirates GP Thinner (only for cleaning tools)
Pot life @25°C	25 Min

### SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

### DRY TIME

Touch Dry	2 - 2.5 hours
Dry to Recoat	8 - 10 hours
Full Dry	24 hours

\*Based on temperatures at 30 degrees Celsius.

\*Humidity, air movement, film thickness and number of coats may impact dry time.

### RECOMMENDED SYSTEM

Emapoxy Primer Sealer	1 Coat
Emapoxy SF Topcoat	2 Coats



## EMAPOXY SF TOPCOAT PIGMENTED

### HEALTH & SAFETY

*Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.*

### STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

### SHELF LIFE

\*For best results, please use within 18 months of the production date.

\*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

### DISCLAIMER

*The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.*

