

NOBLE MATT

PRODUCT DESCRIPTION

Emirates Noble Matt Paint is formulated with pure acrylic emulsion, Engineered with advanced UV protection and exterior durable matt finish.

PRODUCT FEATURES

- Pure Acrylic Formulation
- Enhanced with advanced adhesion and durability
- Advanced anti-carbonation properties
- Enhanced washability
- Low dirt pick up
- UV protection
- Advanced alkali resistance
- Anti-bacterial, anti-fungal, and anti-algae

RECOMMENDED USE

This product is recommended for applications on concrete, cement plaster, brickwork, gypsum board, wood, and masonry surfaces.

*Use for interior and exterior applications like villas, shopping complexes, and high-rise buildings.

TECHNICAL SPECIFICATIONS

Color	Refer to Emirates Paints shade card
Finish	Smooth, Matt
Spreading Rate	10 - 12 m ² / litre
Volume Solids (ASTM d2697)	40 ± 2%
Specific Gravity	1.38 ± 0.02
Dry Film Thickness	40 - 50 Microns / Coat
Wet Film Thickness	80 - 100 Microns / Coat
Packaging Size	3.6L + 18L
Flash Point	Water-Based



NOBLE MATT

APPLICATION DATA

Application Method	Brush, Roller, Spray
Thinner	10% Water maximum by volume depending on the application method
Airless Spray Requirements	Nozzle Size: 0.021" – 0.027" Pressure: 2100 psi Angle of spray: 65° – 80°

SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

DRY TIME

Touch Dry	1 - 2 hours
Dry to Recoat	3 - 4 hours
Full Dry	3 - 5 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Emirates Acrylic Primer WB	1 Coat
Emirates Stucco Filler	2 Coats
Emirates Noble Matt	2 Coats



NOBLE MATT

HEALTH & SAFETY

Water-based paints are generally quite safe to handle with precautions. -General rule- avoid skin and eye contact by wearing overalls, gloves, goggles, masks, etc. Spillage on the skin should immediately be removed by thorough washing with water and soap or a suitable cleaner. The eye should be flushed with fresh water. Avoid inhalation of vapors and paint mist by wearing a suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be applied in a well-ventilated area, and Local safety regulations must be followed.

STORAGE & HANDLING

We highly recommend storing our paint in proper storage conditions as per your local regulations. Keep the paint container sealed and away from direct sunlight and extreme temperatures. Do not keep paint material near any ignition sources. Do not return the half or unused material back to the original container containing the supplied paint to avoid contamination. Handle with care and mix well before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

