

WOOD GLUE

PRODUCT DESCRIPTION

Emirates Wood Glue is a ready-to-use, multi-purpose, high-tack, polyvinyl acetate woodworking glue, designed to give a greater wet tack than white glues, which allows faster gripping action and less slippage during the clamping process.

PRODUCT FEATURES

- Easy removal once cured
- Unaffected by finishes
- Blends with many wood tones
- Easy to refill
- Air-tight seal for long storage life
- Easy to handle
- Excellent flow control

RECOMMENDED USE

This product is recommended to bond porous substrates such as wood, wood compositions, veneer, cardboard, leather, and cork.

*Used for interior and exterior applications.

TECHNICAL SPECIFICATIONS

Color	Translucent pale yellow
Finish	Free-flowing liquid
Spreading Rate	3.9 M ² / Litre
Volume Solids (ASTM d2697)	50 ± 2%
Specific Gravity	1.08
Packaging Size	0.9L + 3.6L
Flash Point	15°C



WOOD GLUE

APPLICATION DATA

Moisture Content	Water (7 – 12% depends on method of application)
Wood Clamp	Pressure: 50 - 150 psi
Mixing Ratio (by weight)	NA
Pot life @30°C	NA

SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

DRY TIME

Open Time	5 minutes
Clamping Time	25 minutes
Dry Time	24 hours

*Based on temperatures at 25 degrees Celsius.

*Humidity, air movement, film thickness, and number of coats may impact dry time.



WOOD GLUE

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

